



DR10H500M (FB)

HALF CELL LINE



HALF-CELL MODULE

The 132 Half Cut module of the Half Cell Line combines the high production efficiency of the half cell technology with an excellent quality / price ratio.

The half-cell configuration improves the electrical distribution inside the panel to increase the yield of the product. For these reasons, the Half Cell Line is suitable not only for industrial installations but also for residential and commercial installations.

30 YEAR LINEAR POWER WARRANTY

25 YEAR PRODUCT WARRANTY



PERC TECHNOLOGY



ANTI-REFLECTIVE GLASS



QBE INSURANCE
Product Liability Insurance QBE

Cells



132 CELLS
MONO 9BB / 10BB M10 HALF | PERC

182 x 91 mm / 7.16 x 3.58"

Frame



COMPACT AND STURDY | 35 mm

ANCHORABLE ALSO ON
THE SHORT SIDE ⁽⁵⁾

HALF CELL LINE

Electrical Characteristics (STC) ⁽¹⁾

DR10H500M (FB)

Nominal Output (Pmax) ⁽²⁾	500 W
Sorting Tolerance	0/+5 W
Voltage at Pmax (Vmp)	38.29 V
Current at Pmax (Imp)	13.06 A
Open Circuit Voltage (Voc) ⁽²⁾	45.45 V
Short Circuit Current (Isc) ⁽²⁾	13.93 A
Maximum System Voltage	1500 V
Maximum Series Fuse Rating	25 A
Module Efficiency	21.06 %
Protection class against electric shock	Class II

Mechanical Characteristics

Solar Cells	132 M10 HALF monocrystalline PERC
Solar Cells Size	182 x 91 mm / 7.16 x 3.58"
Front Cover	3.2 mm / 0.13" thick, low iron tempered glass
Back Cover	TPT (Tedlar-PET-Tedlar)
Encapsulant	EVA (Ethylene vinyl acetate)
Frame	Anodized aluminium alloy, double wall
Frame finishing	Black
Backsheet finishing	Black
Diodes	3 Bypass diodes serviceable
Junction Box	IP68 rated
Connector	MC4 or compatible connector
Cables Length	1200 mm / 47.24"
Cables Section	4.0 mm ² / 0.006 in ²
Dimensions	2094 x 1134 x 35 mm / 82.44 x 44.64 x 1.37"
Weight	26 Kg / 57.3 lbs
Max Load (Test Load) - SF	5400 Pa - 1.5 ⁽³⁾


Temperature Characteristics

NMOT ⁽³⁾	45±2 °C
Temperature Coefficient of Pmax	-0.37 %/°C
Temperature Coefficient of Voc	-0.29 %/°C
Temperature Coefficient of Isc	0.05 %/°C
Operating Temperature	-40 °C - +85°C


Packaging ⁽⁴⁾

Pallet dimensions	2175 x 1155 x 1145 mm / 85.63 x 45.47 x 45.08"
Pieces per pallet	31
Weight	820 kg / 1807.8 lbs

Dimensions



Current/Voltage Characteristics



1. STC: (Standard Test Condition) Irradiance 1000W/m², Module Temperature 25°C, Air Mass 1.5

2. Pmax, Voc, Isc measurement tolerance: ±3%

3. NMOT: Nominal Module Operating Temperature. Irradiance 800W/m², Air 20°C, Wind speed 1m/s

4. Pallets can be stacked up to two

5. Consult the installation manual for the relative mounting configurations